Safety Data Sheet REDUCING SOLVENT-BRUSH



Bulk Sales Reference No.: SDS Revision Date: SDS Revision Number: Y2333N 09/14/2020 A1-8

1. Identification of the	e preparation and company
1.1. Product identifier	
Product Identity	REDUCING SOLVENT-BRUSH
Bulk Sales Reference No.	Y2333N
1.2. Relevant identified uses of the substance or mix	kture and uses advised against
Intended Use	See Technical Data Sheet.
1.3. Details of the supplier of the safety data sheet	
Company Name	Akzo Nobel Coatings
	Manufacturer: Akzo Nobel Coatings International Paint 6001 Antoine Drive Houston, Texas 77091
Emergency	
CHEMTREC	(800) 424-9300
International Paint	(713) 527-3887
Poison Control Center	(800) 854-6813
Customer Service	
International Paint	(800) 589-1267
Fax No.	(800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Acute Tox. 5;H303	May be harmful if swallowed.
Acute Tox. 5;H313	May be harmful in contact with skin.
Skin Irrit. 3;H316	Causes mild skin irritation.
Carc. 2;H351	Suspected of causing cancer.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapor.H303 May be harmful if swallowed.H313 May be harmful in contact with skin.H316 Causes mild skin irritation.H351 Suspected of causing cancer.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves / eye protection / face protection.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P332+313 If skin irritation occurs: Get medical advice/attention.

P370 In case of fire: Use water spray, fog, or regular foam..

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating	Health: 2*	Flammability: 2	Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Methyl Amyl Ketone CAS Number: 0000110-43-0	25 - 50	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H302	[1][2]
Acetic acid, C6-8-branched alky esters CAS Number: 0090438-79-2		Aquatic Chronic 2;H411	[1]
2-Butoxyethyl acetate CAS Number: 0000112-07-2	10 - 25	Acute Tox. 4;H332 Acute Tox. 4;H312	[1][2]
Cyclohexanone CAS Number: 0000108-94-1	10 - 25	Flam. Liq. 3;H226 Acute Tox. 4;H332	[1][2]
PROPRIETARY AROMATIC HYDROCARBONP CAS Number: Proprietary	1.0 - 10	Asp. Tox. 2;H305 Skin Irrit. 2;H315 Eye Dam. 2A;H319	[1]
Naphthalene CAS Number: 0000091-20-3		Carc. 2;H351 Acute Tox. 4;H302 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Y2333N A1

Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.		
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.		
4.2. Most important sy	mptoms and effects, both acute and delayed		
Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.		
Inhalation	Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.		
Eyes	Causes severe eye irritation. Avoid contact with eyes.		
Skin	Causes skin irritation. May be harmful if absorbed through the skin.		
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.		
	5. Fire-fighting measures		

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical. CO2, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses. 127

ERG Guide No.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7.1. Precautions for safe handling

Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discared after each use.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Avoid contact with eyes, skin and clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

CAS No.	Ingredient	Source	Value
0000091-20-3	Naphthalene	OSHA	10 ppm TWA; 50 mg/m3 TWA15 ppm STEL; 75 mg/m3 STEL
		ACGIH	10 ppm TWA
		NIOSH	10 ppm TWA; 50 mg/m3 TWA15 ppm STEL; 75 mg/m3 STEL250 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 ppm TWA
		Mexico	10 ppm TWA VLE-PPT; 50 mg/m3 TWA VLE-PPT15 ppm STEL [PPT-CT]
		Brazil	No Established Limit
0000108-94-1	Cyclohexanone	OSHA	50 ppm TWA; 200 mg/m3 TWA
		ACGIH	20 ppm TWA50 ppm STEL
		NIOSH	25 ppm TWA; 100 mg/m3 TWA700 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA50 ppm STEL
		Mexico	20 ppm TWA VLE-PPT50 ppm STEL [PPT-CT]
		Brazil	No Established Limit
0000110-43-0	Methyl Amyl Ketone	OSHA	100 ppm TWA; 465 mg/m3 TWA
		ACGIH	50 ppm TWA
		NIOSH	100 ppm TWA; 465 mg/m3 TWA800 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	25 ppm TWA; 115 mg/m3 TWA
		Mexico	50 ppm TWA VLE-PPT
		Brazil	No Established Limit
0000112-07-2	2-Butoxyethyl acetate	OSHA	No Established Limit
		ACGIH	20 ppm TWA
		NIOSH	5 ppm TWA; 33 mg/m3 TWA
		Supplier	No Established Limit
		OHSA, CAN	20 ppm TWA
		Mexico	20 ppm TWA VLE-PPT
		Brazil	No Established Limit
0090438-79-2	Acetic acid, C6-8-branched	OSHA	No Established Limit
alkyl	alkyl esters	ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit

		Brazil	No Established Limit
Proprietary	PROPRIETARY AROMATIC	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
	Mexico	No Established Limit	
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000091-20-3	Naphthalene		Hemolysis and eye irritation that causes cataracts
0000108-94-1	Cyclohexanone	NIOSH	Irritation; liver kidney
0000110-43-0	Methyl Amyl Ketone	NIOSH	Irritation; liver kidney
0000112-07-2	2-Butoxyethyl acetate		Adverse effects on blood and hematopoietic system tissue irritation
0090438-79-2	Acetic acid, C6-8-branched alkyl esters	NIOSH	No Established Limit
	PROPRIETARY AROMATIC HYDROCARBONP	NIOSH	No Established Limit

		Ca	rcinogen Data
CAS No.	Ingredient	Source	Value
0000091-20-3	Naphthalene	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000108-94-1	Cyclohexanone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0000110-43-0	Methyl Amyl Ketone	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000112-07-2	2-Butoxyethyl acetate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0090438-79-2	C6-8-branched alkyl	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.

Eyes	Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist before handling this product.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties			
Appearance	Colourless Liquid		
Odor threshold	Not Measured		
рН	No Established Limit		
Melting point / freezing point	Not Measured		
Initial boiling point and boiling range	152 (°C) 305 (°F)		
Flash Point	39 (°C) 102 (°F)		
Evaporation rate (Ether = 1)	Not Measured		
Flammability (solid, gas)	Not Applicable		
Upper/lower flammability or explosive limits	Lower Explosive Limit: .8		
	Upper Explosive Limit: No Established Limit		
vapor pressure (Pa)	Not Measured		
Vapor Density	Heavier than air		
Specific Gravity	0.88		
Solubility in Water	Not Measured		
Partition coefficient n-octanol/water (Log Kow)	Not Measured		
Auto-ignition temperature	Not Measured		
Decomposition temperature	Not Measured		
Viscosity (cSt)	1		
VOC %	Refer to the Technical Data Sheet or label where information is available.		
VOHAP content (gm/litre of paint)	176.62 (as supplied)		
VOHAP content (gm/litre of Solid Coating)	1.77 (as supplied)		

10. Stability and reactivity

10.1. Reactivity
No data available
10.2. Chemical stability
This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
10.3. Possibility of hazardous reactions
No data available
10.4. Conditions to avoid
No data available
10.5. Incompatible materials
Strong oxidizing agents.
10.6. Hazardous decomposition products
No data available

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr
Methyl Amyl Ketone - (110-43-0)	1,670.00, Rat - Category: 4	12,600.00, Rat - Category: NA	No data available	No data available
Acetic acid, C6-8-branched alkyl esters - (90438-79-2)	No data available	No data available	No data available	No data available
2-Butoxyethyl acetate - (112-07-2)	2,400.00, Rat - Category: 5	1,500.00, Rabbit - Category: 4	No data available	No data available
Cyclohexanone - (108-94-1)	1,620.00, Rat - Category: 4	795.00, Rabbit - Category: 3	10.70, Rat - Category: 4	No data available
PROPRIETARY AROMATIC HYDROCARBONP - (Proprietary)	No data available	No data available	No data available	No data available
Naphthalene - (91-20-3)	490.00, Rat - Category: 4	20,000.00, Rabbit - Category: NA	No data available	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	5	May be harmful if swallowed.
Acute Toxicity (skin)	5	May be harmful in contact with skin.
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	2	Suspected of causing cancer.
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12.1. Toxicity

12. Ecological information

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish,	48 hr EC50 crustacea,	ErC50 algae,
	mg/l	mg/l	mg/l
Methyl Amyl Ketone -	131.00, Pimephales	90.20, Daphnia	98.20 (72 hr), Pseudokirchneriella
(110-43-0)	promelas	magna	subcapitata
Acetic acid, C6-8-branched alkyl esters - (90438-79-2)	Not Available	Not Available	0.00 (hr),
2-Butoxyethyl acetate - (112-07-2)	22.00, Fish	303.00, Daphnia magna	501.00 (72 hr), Algae

Cyclohexanone - (108-94-1)	527.00, Pimephales promelas	101.00, Daphnia magna	101.00 (72 hr), Desmodesmus subspicatus
PROPRIETARY AROMATIC HYDROCARBONP - (Proprietary)	Not Available	Not Available	0.00 (hr),
Naphthalene - (91-20-3)	0.99, Oncorhynchus gorbuscha	1.60, Daphnia magna	68.21 (96 hr), Scenedesmus subspicatus

12.2. Persistence and degradability
No data available
12.3. Bioaccumulative potential
Not Measured
12.4. Mobility in soil
No data available
12.5. Results of PBT and vPvB assessment
This product contains no PBT/vPvB chemicals.
12.6. Other adverse effects
No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information 14.1. UN number UN 1263 14.2. UN proper shipping name PAINT RELATED MATERIAL 14.3. Transport hazard class(es) DOT (Domestic Surface Transportation) IMO / IMDG (Ocean Transportation) **Proper Shipping** PAINT RELATED IMDG Proper PAINT RELATED Name MATERIAL Shipping Name MATERIAL Hazard Class 3 - Flammable IMDG Hazard Class 3 - Flammable Sub Class Not applicable UN / NA Number UN 1263 Packing Group Ш IMDG Packing Group III CERCLA/DOT RQ 6797 gal. / 50000 lbs. System Reference 3 Code 14.4. Packing group Ш 14.5. Environmental hazards IMDG Marine Pollutant: No 14.6. Special precautions for user Not Applicable 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA

15. Regulatory information

Inventory. WHMIS Classification B3 D2A DOT Marine Pollutants (10%): (No Product Ingredients Listed) DOT Severe Marine Pollutants (1%): (No Product Ingredients Listed) EPCRA 311/312 Chemicals and RQs (>.1%) : Cyclohexanone (5000 lb final RQ; 2270 kg final RQ) Naphthalene (100 lb final RQ; 45.4 kg final RQ) EPCRA 302 Extremely Hazardous (>.1%) : (No Product Ingredients Listed) EPCRA 313 Toxic Chemicals (>.1%) : Naphthalene Mass RTK Substances (>1%) : Cyclohexanone Methyl Amyl Ketone Penn RTK Substances (>1%) : Cyclohexanone Methyl Amyl Ketone Penn Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) **RCRA Status:** (No Product Ingredients Listed) N.J. RTK Substances (>1%) : Cyclohexanone 2-Butoxyethyl acetate Methyl Amyl Ketone N.J. Special Hazardous Substances (>.01%) : (No Product Ingredients Listed) Naphthalene N.J. Env. Hazardous Substances (>.1%) : Naphthalene Proposition 65 - Carcinogens (>0%): Naphthalene Proposition 65 - Female Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 - Male Repro Toxins (>0%): (No Product Ingredients Listed) Proposition 65 - Developmental Toxins (>0%): (No Product Ingredients Listed) 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H305 May be harmful if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

End of Document