

Material Safety Data Sheet
Brightside Black

Bulk Sales Reference No.:
MSDS Revision Date:
MSDS Revision Number:

Sales
Order: {SalesOrd}
Y4258
10/24/2013
B2-2

1. Identification of the preparation and company
--

1.1. Product identifier

Product Identity	Brightside Black
Bulk Sales Reference No.	Y4258

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Use	See Technical Data Sheet.
Application Method	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Akzo Nobel Coatings International Paint LLC 2270 Morris Avenue P. O. Box 386
--------------	---

Emergency

CHEMTREC (USA)	(800) 424-9300
International Paint	(713) 527-3887
Poison Control Center	(800) 854-681
Customer Service	
International Paint	(800) 589-1267
Fax No.	(800) 631-7481

2. Hazard identification of the product

2.1. Classification of the substance or mixture

Flam. Liq. 3;H226	Flammable liquid and vapor.
Acute Tox. 2;H310	Fatal in contact with skin.
Skin Irrit. 3;H316	Causes mild skin irritation.
Carc. 1B;H350	May cause cancer.
Aquatic Chronic 3;H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



Danger.

H226 Flammable liquid and vapor.
H301 Toxic if swallowed.
H310 Fatal in contact with skin.
H316 Causes mild skin irritation.
H350 May cause cancer.

H412 Harmful to aquatic life with long lasting effects.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P260 Do not breathe mist / vapors / spray.

P262 Do not get in eyes, on skin, or on clothing.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+350 IF ON SKIN: Gently wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a POISON CENTER or doctor / physician.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P370 In case of fire:.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating

Health: 2*

Flammability: 2

Reactivity: 0

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Solvent naphtha (petroleum), medium aliphatic CAS Number: 0064742-88-7	10 - 25	Asp. Tox. 1;H304	[1]
Stoddard solvent CAS Number: 0008052-41-3	10 - 25	Asp. Tox. 1;H304	[1][2]
Petroleum distillates, hydrotreated light CAS Number: 0064742-47-8	1.0 - 10	Asp. Tox. 1;H304	[1]
Dimethyl glutarate CAS Number: 0001119-40-0	1.0 - 10	----	[1]
Carbon black CAS Number: 0001333-86-4	1.0 - 10	----	[1][2]
Naphtha (petroleum), heavy aromatic CAS Number: 0064742-94-5	1.0 - 10	Asp. Tox. 1;H304	[1]
Xylenes (o-, m-, p- isomers) CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]
SATURATED HYDROCARBON CAS Number: TS-KS6505	1.0 - 10	----	[1]
Naphthalene CAS Number: 0000091-20-3	0.10 - 1.0	Carc. 2;H351 Acute Tox. 4;H302 Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1][2]
2,2'-Bipyridine CAS Number: 0000366-18-7	0.10 - 1.0	Acute Tox. 4;H312 Acute Tox. 3;H301 Aquatic Chronic	[1]

		3;H412	
Methyl ethyl ketoxime CAS Number: 0000096-29-7	0.10 - 1.0	Carc. 2;H351 Acute Tox. 4;H312 Eye Dam. 1;H318 Skin Sens. 1;H317	[1]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

4. First aid measures

4.1. Description of first aid measures

General	Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin	In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately.
Ingestion	If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Overview	NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing.
Inhalation	Harmful if inhaled. Causes lung irritation. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea.
Eyes	Causes severe eye irritation. Avoid contact with eyes.
Skin	Causes skin irritation. May be harmful if absorbed through the skin.
Ingestion	Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness.
Chronic effects	Possible cancer hazard. Contains an ingredient which may cause cancer based on animal data (See Section 2 and Section 15 for each ingredient). Risk of cancer depends on duration and level of exposure.

5. Fire-fighting measures

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. SMALL FIRES: Use dry chemical, CO₂, water spray or alcohol-resistant foam. LARGE FIRES: Use water spray, fog, or alcohol-resistant foam. Do not use straight streams. Move containers from fire area if you can do so without risk. Runoff from fire control may cause pollution. Dike fire control water for later disposal. Do not scatter the material.

5.2. Special hazards arising from the substance or mixture

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or

Y4258_B2

other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 25 to 50 meters (80 to 160 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Vapors may cause flash fire or ignite explosively.

In Storage

Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilities

Store between 40-100F (4-38C).

Do not get in eyes, on skin or clothing.

Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000091-20-3	Naphthalene	OSHA	10 ppm TWA; 50 mg/m3 TWA15 ppm STEL; 75 mg/m3 STEL
		ACGIH	10 ppm TWA15 ppm STEL
		NIOSH	10 ppm TWA; 50 mg/m3 TWA15 ppm STEL; 75 mg/m3 STEL250 ppm IDLH
		Supplier	No Established Limit
		OHSA, CAN	10 ppm TWA15 ppm STEL
		Mexico	10 ppm TWA LMPE-PPT; 50 mg/m3 TWA LMPE-PPT15 ppm STEL [LMPE-CT]; 75 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0000096-29-7	Methyl ethyl ketoxime	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0000366-18-7	2,2'-Bipyridine	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Y4258_B2

		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0001119-40-0	Dimethyl glutarate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL
		ACGIH	100 ppm TWA150 ppm STEL
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	100 ppm TWA150 ppm STEL
		Mexico	100 ppm TWA LMPE-PPT; 435 mg/m3 TWA LMPE-PPT150 ppm STEL [LMPE-CT]; 655 mg/m3 STEL [LMPE-CT]
		Brazil	78 ppm TWA LT; 340 mg/m3 TWA LT
0001333-86-4	Carbon black	OSHA	3.5 mg/m3 TWA
		ACGIH	3 mg/m3 TWA (inhalable fraction)
		NIOSH	3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as 1750 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	3 mg/m3 TWA (inhalable)
		Mexico	3.5 mg/m3 TWA LMPE-PPT7 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	500 ppm TWA; 2900 mg/m3 TWA
		ACGIH	100 ppm TWA
		NIOSH	350 mg/m3 TWA1800 mg/m3 Ceiling (15 min)20000 mg/m3 IDLH
		Supplier	No Established Limit
		OHSA, CAN	525 mg/m3 TWA (140C Flash aliphatic solvent)
		Mexico	100 ppm TWA LMPE-PPT; 523 mg/m3 TWA LMPE-PPT200 ppm STEL [LMPE-CT]; 1050 mg/m3 STEL [LMPE-CT]
		Brazil	No Established Limit
0064742-47-8	Petroleum distillates, hydrotreated light	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit

Y4258_B2

		Mexico	No Established Limit
		Brazil	No Established Limit
0064742-94-5	Naphtha (petroleum), heavy aromatic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit
TS-KS6505	SATURATED HYDROCARBON	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
		OHSA, CAN	No Established Limit
		Mexico	No Established Limit
		Brazil	No Established Limit

Health Data

CAS No.	Ingredient	Source	Value
0000091-20-3	Naphthalene	NIOSH	Hemolysis and eye irritation that causes cataracts
0000096-29-7	Methyl ethyl ketoxime	NIOSH	No Established Limit
0000366-18-7	2,2'-Bipyridine	NIOSH	No Established Limit
0001119-40-0	Dimethyl glutarate	NIOSH	No Established Limit
0001330-20-7	Xylenes (o-, m-, p- isomers)	NIOSH	Central nervous system depressant; respiratory and eye irritation
0001333-86-4	Carbon black	NIOSH	Lung cardiovascular
0008052-41-3	Stoddard solvent	NIOSH	Eye nose
0064742-47-8	Petroleum distillates, hydrotreated light	NIOSH	No Established Limit
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic	NIOSH	No Established Limit
0064742-94-5	Naphtha (petroleum), heavy aromatic	NIOSH	No Established Limit
TS-KS6505	SATURATED HYDROCARBON	NIOSH	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0000091-20-3	Naphthalene	OSHA	Select Carcinogen: Yes
		NTP	Known: No; Suspected: Yes
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0000096-29-7	Methyl ethyl ketoxime	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0000366-18-7	2,2'-Bipyridine	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001119-40-0	Dimethyl glutarate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylenes (o-, m-, p- isomers)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0001333-86-4	Carbon black	OSHA	Select Carcinogen: Yes

Y4258_B2

		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-47-8	Petroleum distillates, hydrotreated light	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-88-7	Solvent naphtha (petroleum), medium aliphatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-94-5	Naphtha (petroleum), heavy aromatic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
TS-KS6505	SATURATED HYDROCARBON	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

8.2. Exposure controls

Respiratory	Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet.
Eyes	Avoid contact with eyes. Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, safety glasses, chemical goggles, and/or head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Skin	Protective equipment should be selected to provide protection from exposure to the chemicals listed in Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discarded after each use.
Engineering Controls	Depending on the site-specific conditions of use, provide adequate ventilation.
Other Work Practices	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water.

9. Physical and chemical properties

Appearance	Black Liquid
Odour threshold	Not Measured
pH	No Established Limit
Melting point / freezing point	Not Measured
Initial boiling point and boiling range	146 (C) 295 (F)
Flash Point	41 (C) 105 (F)
Evaporation rate (Ether = 1)	Not Measured

Y4258_B2

Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: .7 Upper Explosive Limit: No Established Limit
vapor pressure (Pa)	Not Measured
Vapor Density	Heavier than air
Specific Gravity	0.94
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	No Established Limit
VOC %	Refer to the Technical Data Sheet or label where information is available.
VOHAP content (gm/litre of paint)	64.00 (as supplied)
VOHAP content (gm/litre of Solid Coating)	27.94 (as supplied)

9.2. Other information

No further information

10. Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	6,000.00, Rat - Category: NA	3,000.00, Rabbit - Category: 5	No data available	No data available
Stoddard solvent - (8052-41-3)	No data available	No data available	No data available	No data available
Petroleum distillates, hydrotreated light - (64742-47-8)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available
Dimethyl glutarate - (1119-40-0)	8,191.00, Rat - Category: NA	3,400.00, Rabbit - Category: 5	No data available	No data available
Carbon black - (1333-86-4)	8,000.00, Rat - Category: NA	3.00, Rabbit - Category: 1	No data available	No data available

Y4258_B2

Naphtha (petroleum), heavy aromatic - (64742-94-5)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available
Xylenes (o-, m-, p- isomers) - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available
SATURATED HYDROCARBON - (TS-KS6505)	No data available	No data available	No data available	No data available
Naphthalene - (91-20-3)	490.00, Rat - Category: 4	20,000.00, Rabbit - Category: NA	No data available	No data available
2,2'-Bipyridine - (366-18-7)	100.00, Rat - Category: 3	400.00, Rat - Category: 3	No data available	No data available
Methyl ethyl ketoxime - (96-29-7)	930.00, Rat - Category: 4	2,000.00, Rabbit - Category: 4	20.00, Rat - Category: 4	No data available

Item	Category	Hazard
Acute Toxicity (mouth)	Not Classified	Not Applicable
Acute Toxicity (skin)	2	Fatal in contact with skin.
Acute Toxicity (inhalation)	Not Classified	Not Applicable
Skin corrosion/irritation	3	Causes mild skin irritation.
Eye damage/irritation	Not Classified	Not Applicable
Sensitization (respiratory)	Not Classified	Not Applicable
Sensitization (skin)	Not Classified	Not Applicable
Germ toxicity	Not Classified	Not Applicable
Carcinogenicity	1B	May cause cancer.
Reproductive Toxicity	Not Classified	Not Applicable
Specific target organ systemic toxicity (single exposure)	Not Classified	Not Applicable
Specific target organ systemic Toxicity (repeated exposure)	Not Classified	Not Applicable
Aspiration hazard	Not Classified	Not Applicable

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Solvent naphtha (petroleum), medium aliphatic - (64742-88-7)	800.00, Pimephales promelas	100.00, Daphnia magna	450.00 (96 hr), Selenastrum capricornutum
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available
Petroleum distillates, hydrotreated light - (64742-47-8)	2.20, Lepomis macrochirus	4,720.00, Dendronereides heteropoda	Not Available
Dimethyl glutarate - (1119-40-0)	19.60, Pimephales promelas	122.10, Daphnia magna	Not Available
Carbon black - (1333-86-4)	1,000.00, Danio rerio	5,600.00, Daphnia magna	10,000.00 (72 hr), Scenedesmus subspicatus
Naphtha (petroleum), heavy aromatic - (64742-94-5)	45.00, Pimephales promelas	12.00, Daphnia magna	2.50 (72 hr), Skeletonema costatum
Xylenes (o-, m-, p- isomers) - (1330-20-7)	3.30, Oncorhynchus	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales

Y4258_B2

	mykiss		
SATURATED HYDROCARBON - (TS-KS6505)	Not Available	Not Available	Not Available
Naphthalene - (91-20-3)	0.99, Oncorhynchus gorbuscha	1.60, Daphnia magna	68.21 (96 hr), Scenedesmus subspicatus
2,2'-Bipyridine - (366-18-7)	Not Available	Not Available	Not Available
Methyl ethyl ketoxime - (96-29-7)	320.00, Leuciscus idus	500.00, Daphnia magna	83.00 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

14. Transport information

14.1. UN number UN 1263

14.2. UN proper shipping name Paint

14.3. Transport hazard class(es)

DOT (Domestic Surface Transportation)		IMO / IMDG (Ocean Transportation)	
DOT Proper Shipping Name	CONSUMER COMMODITY, ORM-D	IMDG Proper Shipping Name	Paint
DOT Hazard Class	Not Regulated	IMDG Hazard Class Sub Class	Flammable Liquid, 3 Not applicable
UN / NA Number	UN 1263	IMDG Packing Group	III
DOT Packing Group	Not Regulated	System Reference Code	181
CERCLA/DOT RQ	565 gal. / 4414 lbs.		

14.4. Packing group III

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

15. Regulatory information

Y4258_B2

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory.

WHMIS Classification B3 D2A

DOT Marine Pollutants (10%):
(No Product Ingredients Listed)

DOT Severe Marine Pollutants (1%):
(No Product Ingredients Listed)

EPCRA 311/312 Chemicals and RQs (>.1%) :

- Benzene, ethyl- (1000 lb final RQ; 454 kg final RQ)
- Naphthalene (100 lb final RQ; 45.4 kg final RQ)
- Xylenes (o-, m-, p- isomers) (100 lb final RQ; 45.4 kg final RQ)

EPCRA 302 Extremely Hazardous (>.1%) :
(No Product Ingredients Listed)

EPCRA 313 Toxic Chemicals (>.1%) :

- 1,2,4-Trimethyl benzene
- Benzene, ethyl-
- Naphthalene
- Xylenes (o-, m-, p- isomers)

Mass RTK Substances (>1%) :

- Carbon black
- Stoddard solvent
- Xylenes (o-, m-, p- isomers)

Penn RTK Substances (>1%) :

- Carbon black
- Stoddard solvent
- Xylenes (o-, m-, p- isomers)

Penn Special Hazardous Substances (>.01%) :
(No Product Ingredients Listed)

RCRA Status:
(No Product Ingredients Listed)

N.J. RTK Substances (>1%) :

- Carbon black
- Solvent naphtha (petroleum), medium aliphatic
- Stoddard solvent
- Xylenes (o-, m-, p- isomers)

N.J. Special Hazardous Substances (>.01%) :

- 2-Butoxyethanol
- Carbon black
- Benzene, ethyl-
- Naphthalene
- Solvent naphtha (petroleum), medium aliphatic
- Xylenes (o-, m-, p- isomers)

N.J. Env. Hazardous Substances (>.1%) :

- 1,2,4-Trimethyl benzene
- Benzene, ethyl-
- Naphthalene
- Xylenes (o-, m-, p- isomers)

Proposition 65 - Carcinogens (>0%):

- Carbon black
- Benzene, ethyl-
- Naphthalene

Proposition 65 - Female Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Male Repro Toxins (>0%):
(No Product Ingredients Listed)

Proposition 65 - Developmental Toxins (>0%):
(No Product Ingredients Listed)

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

- H226 Flammable liquid and vapor.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

The following sections have changed since the previous revision.

SECTION 9: Physical and chemical properties

SECTION 12: Ecological information

End of Document