Safety Data Sheet PERFECTION JET BLACK

Bulk Sales Reference No.: SDS Revision Date: SDS Revision Number: YHY999 04/15/2021 E1-3

| 1. Identification of the preparation and company | | | | |
|--|--|--|--|--|
| 1.1. Product identifier | | | | |
| Product Identity | PERFECTION JET BLACK | | | |
| Bulk Sales Reference No. | YHY999 | | | |
| 1.2. Relevant identified uses of the substa | ance or mixture and uses advised against | | | |
| Intended Use | See Technical Data Sheet. | | | |
| 1.3. Details of the supplier of the safety da | ata sheet | | | |
| Company Name | Akzo Nobel Coatings | | | |
| | Manufacturer: | | | |
| | Akzo Nobel Coatings International Paint | | | |
| | 6001 Antoine Drive | | | |
| | Houston, Texas 77091 | | | |
| Emergency | | | | |
| CHEMTREC | (800) 424-9300 | | | |
| International Paint | (713) 527-3887 | | | |
| Poison Control Center | (800) 854-6813 | | | |
| Customer Service | | | | |
| International Paint | (800) 589-1267 | | | |
| Fax No. | (800) 631-7481 | | | |

2.1. Classification of the substance or mixture

| Flam. Liq. 3;H226 | Flammable liquid and vapor. |
|------------------------|--|
| Skin Irrit. 3;H316 | Causes mild skin irritation. |
| Eye Irrit. 2;H319 | Causes serious eye irritation. |
| Skin Sens. 1;H317 | May cause an allergic skin reaction. |
| Aquatic Chronic 2;H411 | Toxic to aquatic life with long lasting effects. |

2.2. Label elements

Using the Toxicity Data listed in section 11 & 12 the product is labelled as follows.



H226 Flammable liquid and vapor.

H316 Causes mild skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P235 Keep cool.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash area of contact thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+352 IF ON SKIN: Wash with soap and water.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P332+313 If skin irritation occurs: Get medical advice/attention.

P333 If skin irritation or a rash occurs:.

P337+313 If eye irritation persists: Get medical advice / attention.

P363 Wash contaminated clothing before reuse.

P370 In case of fire: Use water spray, fog, or regular foam..

Health: 2

P391 Collect spillage.

P403+233 Store in a well ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with local / national regulations.

HMIS Rating

Flammability: 2

Reactivity: 0

Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

| | Ingredient/Chemical Designations | Weight % | GHS Classification | Notes |
|-----------------------------------|--|---------------|---|--------|
| 3-Methoxybutyl ac CAS Number: | cetate 0004435-53-4 | | Eye Irrit. 2;H319 | [1] |
| 2-Methoxy-1-Meth CAS Number: | nylethyl Acetate 0000108-65-6 | | Flam. Liq. 3;H226 | [1] |
| Xylene CAS Number: | 0001330-20-7 | 10 | Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315 | [1][2] |
| Carbon black CAS Number: | 0001333-86-4 | 1.0 - 10 | Not Classified | [1][2] |
| | benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omeg | 0.10 - 1.0 | Skin Sens. 1;H317 | [1] |
| Benzotriazol deriv CAS Number: | | 1.0 | Skin Sens. 1;H317 Aquatic Chronic 2;H411 | [1] |

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

YHY999_E1

| | 4. First aid measures |
|-------------------|---|
| 4.1 Description | of first aid measures |
| General | Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly clean or destroy contaminated shoes. |
| Inhalation | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. |
| Eyes | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. |
| Skin | In case of contact, immediately flush skin with soap and plenty of water. Get medical attention immediately. |
| Ingestion | If swallowed, immediately contact Poison Control Center at 1-800-854-6813. DO NOT induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to an unconscious person. |
| 4.2. Most importa | ant symptoms and effects, both acute and delayed |
| Overview | NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid contact with eyes, skin and clothing. |
| Inhalation | Harmful if inhaled. Causes nose and throat irritation. Vapors may affect the brain or nervous system causing dizziness, headache or nausea. |
| Eyes | Causes severe eye irritation. Avoid contact with eyes. |
| Skin | Causes skin irritation. May be harmful if absorbed through the skin. |
| Ingestion | Harmful if swallowed. May cause abdominal pain, nausea, vomiting, diarrhea, or drowsiness. |
| | 5. Fire-fighting measures |

5.1. Extinguishing media

CAUTION: This product has a very low flashpoint. Use of water spray when fighting fire may be inefficient. CAUTION: For mixtures containing alcohol or polar solvent, alcohol-resistant foam may be more effective. SMALL FIRES: Use dry chemical, CO2, water spray or regular foam. LARGE FIRES: Use water spray, fog, or regular foam. Do not use straight streams. Move containers from fire area if you can do so without risk.

5.2. Special hazards arising from the substance or mixture

No data available

5.3. Advice for fire-fighters

Cool closed containers exposed to fire by spraying them with water. Do not allow run off water and contaminants from fire fighting to enter drains or water courses.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

ELIMINATE ALL IGNITION SOURCES (no smoking, flares, sparks or flames in immediate area). Use only non-sparking equipment to handle spilled material and absorbent. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, basements or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to containers. Use non-sparking tools to collect absorbed material.

6.2. Environmental precautions

Do not allow spills to enter drains or watercourses.

6.3. Methods and material for containment and cleaning up

CALL CHEMTREC at (800)-424-9300 for emergency response. Isolate spill or leak area immediately for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas. Ventilate closed spaces before entering. LARGE SPILLS: Consider initial downwind evacuation for at least 300 meters (1000 feet).

7. Handling and storage

7.1. Precautions for safe handling

Handling

Protective equipment should be selected to provide protection from exposure to the chemicals listed in

Section 3 of this document. Depending on the site-specific conditions of use, protective gloves, apron, boots, head and face protection may be required to prevent contact. The equipment must be thoroughly cleaned, or discared after each use.

In Storage Keep away from heat, sparks and flame.

7.2. Conditions for safe storage, including any incompatibilitiesStore between 40-100F (4-38C).Avoid contact with eyes, skin and clothing.Strong oxidizing agents.

Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone.

7.3. Specific end use(s)

Close container after each use.

Wash thoroughly after handling.

Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation.

| | | 1 | |
|--------------|--|--------------|--|
| | 8. Exposure controls and personal protection | | |
| | 8.1. Control parameters Exposure | | |
| CAS No. | Ingredient | Source | Value |
| | | | No Established Limit |
| | | ACGIH | No Established Limit |
| | | | No Established Limit |
| | | Supplier | No Established Limit |
| | | | 50 ppm TWA; 270 mg/m3 TWA |
| | | | No Established Limit |
| | | Brazil | No Established Limit |
| 0001330-20-7 | Xylene | OSHA | 100 ppm TWA; 435 mg/m3 TWA150 ppm STEL; 655 mg/m3 STEL |
| | | ACGIH | 100 ppm TWA150 ppm STEL |
| | | NIOSH | No Established Limit |
| | | | No Established Limit |
| | | OHSA, CAN | 100 ppm TWA150 ppm STEL |
| | | Mexico | 100 ppm TWA VLE-PPT150 ppm STEL [PPT-CT] |
| | | Brazil | 78 ppm TWA LT; 340 mg/m3 TWA LT |

YHY999_E1

| 0001333-86-4 | Carbon black | OSHA | 3.5 mg/m3 TWA |
|--------------|---|--------------|---|
| | | ACGIH | 3 mg/m3 TWA (inhalable particulate matter) |
| | | NIOSH | 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as 1750 mg/m3 IDLH |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | 3 mg/m3 TWA (inhalable) |
| | | Mexico | 3 mg/m3 TWA VLE-PPT (inhalable fraction) |
| | | Brazil | No Established Limit |
| 0004435-53-4 | 3-Methoxybutyl acetate | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | Supplier | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0104810-47-1 | Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omeg | OSHA | No Established Limit |
| | | | No Established Limit |
| | | NIOSH | No Established Limit |
| | | | No Established Limit |
| | | OHSA, CAN | No Established Limit |
| | | Mexico | No Established Limit |
| | | Brazil | No Established Limit |
| 0104810-48-2 | Benzotriazol derivative | OSHA | No Established Limit |
| | | ACGIH | No Established Limit |
| | | NIOSH | No Established Limit |
| | | | No Established Limit |
| | | OHSA, CAN | No Established Limit |

| | No Established Limit |
|--|-------------------------|
| | No Established Limit |

| | Health Data | | |
|--------------|---|--------|--|
| CAS No. | Ingredient | Source | Value |
| 0000108-65-6 | 2-Methoxy-1-Methylethyl Acetate | NIOSH | No Established Limit |
| 0001330-20-7 | Xylene | | Central nervous system depressant; respiratory and eye irritation |
| 0001333-86-4 | Carbon black | NIOSH | Lung cardiovascular |
| 0004435-53-4 | 3-Methoxybutyl acetate | NIOSH | No Established Limit |
| 0104810-47-1 | Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omeg | | No Established Limit |
| 0104810-48-2 | Benzotriazol derivative | NIOSH | No Established Limit |

| CAS No. | Ingredient | Source | Value |
|--------------|--|--------|---|
| | | | |
| 0000108-65-6 | | | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0001330-20-7 | Xylene | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No; |
| 0001333-86-4 | Carbon black | | Select Carcinogen: Yes |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No; |
| 0004435-53-4 | 3-Methoxybutyl acetate | | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0104810-47-1 | Poly(oxy-1,2-ethanediyl), | OSHA | Select Carcinogen: No |
| | .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omeg | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No; |
| 0104810-48-2 | Benzotriazol derivative | OSHA | Select Carcinogen: No |
| | | NTP | Known: No; Suspected: No |
| | | IARC | Group 1: No; Group 2a: No; |
| | | | Group 2b: No; Group 3: No; Group 4: No; |

8.2. Exposure controls

Respiratory

Select equipment to provide protection from the ingredients listed in Section 3 of this document. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates dust, vapor, or mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. FOR USERS OF 3M RESPIRATORY PROTECTION ONLY: For information and assistance on 3M occupational health and safety

| | products, call OH&ESD Technical Service toll free in U.S.A. 1-800-243-4630, in Canada call 1-800-267-4414. Please do not contact these numbers regarding other manufacturer's respiratory protection products. 3M does not endorse the accuracy of the information contained in this Material Safety Data Sheet. |
|----------------------|---|
| Eyes | Avoid contact with eyes. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products. When there is a risk of ignition from static electricity, wear antistatic protective clothing and footwear. Any additional personal protective equipment or measures should be selected based on the risk assessment of the task being performed and should be approved by a specialist before handling this product. |
| Engineering Controls | Depending on the site-specific conditions of use, provide adequate ventilation. |
| Other Work Practices | Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use good personal hygiene practices. Wash hands before eating, drinking, using toilet facilities, etc. Promptly remove soiled clothing and wash clothing thoroughly before reuse. Shower after work using plenty of soap and water. |

| 9. Physical and chemical properties | | | | | |
|---|--|--|--|--|--|
| | | | | | |
| Appearance | Black Liquid | | | | |
| Odor threshold | Not Measured | | | | |
| рН | No Established Limit | | | | |
| Melting point / freezing point | Not Measured | | | | |
| Initial boiling point and boiling range | 124 (°C) 255 (°F) | | | | |
| Flash Point | 47 (°C) 117 (°F) | | | | |
| Evaporation rate (Ether = 1) | Not Measured | | | | |
| Flammability (solid, gas) | Not Applicable | | | | |
| Upper/lower flammability or explosive limits | s Lower Explosive Limit: .8 | | | | |
| | Upper Explosive Limit: No Established Limit | | | | |
| vapor pressure (Pa) | Not Measured | | | | |
| Vapor Density | Heavier than air | | | | |
| Specific Gravity | 1.07 | | | | |
| Solubility in Water | Not Measured | | | | |
| Partition coefficient n-octanol/water (Log Kow) | Not Measured | | | | |
| Auto-ignition temperature | Not Measured | | | | |
| Decomposition temperature | Not Measured | | | | |
| Viscosity (cSt) | No Established Limit Not Measured | | | | |
| VOC % | Refer to the Technical Data Sheet or label where information is available. | | | | |
| VOHAP content (gm/litre of paint) | 85.40 (as supplied) | | | | |
| VOHAP content (gm/litre of Solid Coating) | 30.51 (as supplied) | | | | |

10. Stability and reactivity

10.1. Reactivity
No data available
10.2. Chemical stability
This product is stable and hazardous polymerization will not occur. Not sensitive to mechanical impact. Excessive heat and fumes generation can occur if improperly handled.
10.3. Possibility of hazardous reactions
No data available
10.4. Conditions to avoid
No data available
10.5. Incompatible materials

Strong oxidizing agents. 10.6. Hazardous decomposition products No data available

11. Toxicological information

Acute toxicity

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

| Ingredient | Oral LD50, mg/kg | Skin LD50, mg/kg | Inhalation Vapor LC50, mg/L/4hr | Inhalation Dust/Mist LC50 mg/L/4hr |
|--|---------------------------------------|--------------------------------------|---------------------------------------|--|
| 3-Methoxybutyl acetate - (4435-53-4) | 4,210.00, Rat - Category: 5 | No data available | No data available | No data availab |
| 2-Methoxy-1-Methylethyl Acetate - (108-65-6) | 6,190.00, Rat - Category: NA | 2,001.00, Rabbit - Category: 5 | No data available | No data availab |
| Xylene - (1330-20-7) | 4,299.00, Rat - Category: 5 | 1,548.00, Rabbit - Category: 4 | No data available | 20.00, Rat - Category: NA |
| Carbon black - (1333-86-4) | 8,001.00, Rat - Category: NA | No data available | No data available | No data availab |
| Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omeg - (104810-47-1) | No data available | No data available | No data available | No data availab |
| Benzotriazol derivative - (104810-48-2) | 2,000.00, Rat - Category: 4 | 2,000.00, Rat - Category: 4 | No data available | No data availab |

| ltem | Category | Hazard |
|--|----------------|--------------------------------------|
| Acute Toxicity (mouth) | Not Classified | Not Applicable |
| Acute Toxicity (skin) | Not Classified | Not Applicable |
| Acute Toxicity (inhalation) | Not Classified | Not Applicable |
| Skin corrosion/irritation | 3 | Causes mild skin irritation. |
| Eye damage/irritation | 2 | Causes serious eye irritation. |
| Sensitization (respiratory) | Not Classified | Not Applicable |
| Sensitization (skin) | 1 | May cause an allergic skin reaction. |
| Germ toxicity | Not Classified | Not Applicable |
| Carcinogenicity | Not Classified | Not Applicable |
| Reproductive Toxicity | Not Classified | Not Applicable |
| Specific target organ systemic Toxicity (repeated exposure) | Not Classified | Not Applicable |
| Aspiration hazard | Not Classified | Not Applicable |

12. Ecological information

12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

| Ingredient | 96 hr LC50 fish, mg/l | 48 hr EC50 crustacea, mg/l | |
|--|--------------------------------|-------------------------------|---------|
| 3-Methoxybutyl acetate - (4435-53-4) | 7.10, Danio rerio | 360.00, Daphnia magna | |
| 2-Methoxy-1-Methylethyl Acetate - (108-65-6) | 100.00, Oncorhynchus mykiss | 501.00, Daphnia magna | 1,001.0 |
| Xylene - (1330-20-7) | 3.30, Oncorhynchus mykiss | 8.50, Palaemonetes pugio | 100. |
| Carbon black - (1333-86-4) | 1,000.00, Danio rerio | Not Available | 10,0 |
| Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]omeg - (104810-47-1) | Not Available | Not Available | |
| Benzotriazol derivative - (104810-48-2) | 2.80, Pisces | 3.80, Daphnia magna | |

12.2. Persistence and degradability
No data available
12.3. Bioaccumulative potential
Not Measured
12.4. Mobility in soil
No data available
12.5. Results of PBT and vPvB assessment
This product contains no PBT/vPvB chemicals.
12.6. Other adverse effects
No data available

13. Disposal considerations

13.1. Waste treatment methods

Do not allow spills to enter drains or watercourses.

Dispose of in accordance with local, state and federal regulations. (Also reference RCRA information in Section 15 if listed).

| 14. Transport information | | | | | |
|---------------------------------------|--------------------------------|-----------------------------------|---------------------------------|--|--|
| | | | | | |
| 14.1. UN number | UN 1263 | | | | |
| 14.2. UN proper shipping name PAINT | | | | | |
| 14.3. Transport hazard clas | s(es) | | | | |
| DOT (Domestic Surface Transportation) | | IMO / IMDG (Ocean Transportation) | | | |
| Proper Shipping Name | PAINT | IMDG Proper Shipping Name | PAINT | | |
| Hazard Class | 3 - Flammable | IMDG Hazard Class Sub Class | 3 - Flammable Not applicable | | |
| UN / NA Number | UN 1263 | | | | |
| Packing Group | III | IMDG Packing Group | III | | |
| CERCLA/DOT RQ | 394 gal. / 3514 lbs. | System Reference Code | 2 | | |
| 14.4. Packing group | Ш | | | | |
| 14.5. Environmental hazard | s | | | | |
| IMDG Marine Pol | lutant: Yes (3-Methoxybutyl a | cetate) | | | |
| 14.6. Special precautions for | | | | | |
| | | | | | |

Not Applicable

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not Applicable

| | 15. Regulatory information | | |
|---|--|--|--|
| Regulatory Overview | The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented. All ingredients of this product are listed on the TSCA (Toxic Substance Control Act) Inventory or are not required to be listed on the TSCA Inventory. | | |
| WHMIS Classification | B3 D2B | | |
| DOT Marine Pollutants (No Product Ingr | | | |
| DOT Severe Marine Po (No Product Ingr | | | |
| EPCRA 311/312 Chem | nicals and RQs (>.1%): | | |
| N-Butyl Acetate (listed under Buty | (5000 lb final RQ (listed under Butyl acetate); 2270 kg final RQ vl acetate)) | | |
| Xylene (100 lb | final RQ; 45.4 kg final RQ) | | |
| EPCRA 302 Extremely (No Product Ingr | | | |
| EPCRA 313 Toxic Che | micals (>.1%) : | | |
| Xylene | | | |
| Mass RTK Substances | s (>1%) : | | |
| Carbon black | | | |
| Xylene | | | |
| Penn RTK Substances | (>1%) : | | |
| Carbon black | | | |
| Xylene | | | |
| Penn Special Hazardo | us Substances (>.01%) : | | |
| Carbon black | | | |
| RCRA Status: | | | |
| (No Product Ingr | edients Listed) | | |
| N.J. RTK Substances (| | | |
| 3-Methoxybutyl acetate | | | |
| Carbon black | | | |
| Xylene | | | |
| | s Substances (>.01%) : | | |
| N-Butyl Acetate | | | |
| Carbon black | | | |
| Xylene | | | |
| N.J. Env. Hazardous S | ubstances (> 1%) : | | |
| Xylene | | | |
| Proposition 65 - Carcin | ngens (>0%). | | |
| Carbon black | | | |
| Proposition 65 - Femal (No Product Ingr | | | |
| Proposition 65 - Male F (No Product Ingr | Repro Toxins (>0%): | | |
| | opmental Toxins (>0%): | | |
| | 16. Other information | | |

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders. The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

End of Document